


SECTION A-A

2		1	
REV	CONTENT	CHK	DATE
V0.0	CONTENT	LZW	24.08.05

Electrical :

	UL	IEC
1.Rated Voltage :	300V	250V
2.Rated Current :	12A	20A
3.Torque Value :	M3 , 4.43Lb.in	M3 , 0.5N.m
4.Wire Range:	26-12AWG	0.5-2.5mm ²
5.Stripping Length :	6-7mm	
6.Withstanding Voltage :	AC2000V/1Min.	
7.Operating Temperature :	-40°C~+105°C	
8.RoHS Compliance		
9."★" is the key quality control point.		

GT130 - 5.0 - XXP - X X - 00



- ① Series No. ④ 1 Single Pitch
 2 Double Pitch
- ② Pitch ⑤ Color: 1 Grey
 2 Blue
 3 Black
 4 Green
③ Poles 5 Orange
 02 02Contacts 6 Red
 03 03Contacts 7 Transparent
 ... 8 Yellow
 24 24Contacts 9 White
- ⑥ Customer Request : 00--Standard

4	SCREW		XX		P	Steel		Zn Plated		
3	BLOCK		XX		P	COPPER ALLOY		Ni Plated		
2	PIN		XX		P	COPPER ALLOY		Tin Plated		
1	HOUSING		XX		1	PA66(UL94V-0)		SEE NOTE		
ITEM	NAME OF PART		NO. OF PART		Q"TY	MATERIAL		NOTE		
DWG.	LZW	DATE	24.08.05		SIZE	A4	UNITS	mm	SHEET/OF	1 / 1
CHK.		DATE			SCALE	1:1				
APP.		DATE			NAME	GT130-5.0-XXP-XX-00				
		NINGBO GOLTEN ELECTRONICS CO., LTD								
					DWGNO.	XXXXX				