


Push-in terminal block-UJ6-1.5 - 421482



Push-in terminal block , rated voltage:500V , Max. operating current:17.5A, connection method : spring connection , number of connections : 2 , crimping range : 0.2mm² -1.5 mm² , AWG : 24-16 , thickness:3.5mm , height:30.5mm , color : grey , mounting type : TH35-7.5、TH35-15

Product parameter

Parameter	Data
Packing unit (PCS)	100
NW per piece(g)	3.2
Layers	1
Number of connections	2
Rated cross section(mm ²)	1.5
Color	grey
Insulation material	PA
Flame retardant grade	V0
Rated voltage(V)	500
Rated current(A)	17.5
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	RoHS

Technical data

Parameter	Data
-----------	------

Parameter	Data
Connection Method	Spring connection
Stripping length(mm)	11
Stranded conductors(mm ²)	0.2-1.5
Stranded conductors AWG	24-16
Connection in acc. with standard	IEC 60947-7-1
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%

Dimension

Parameter	Data
Width(mm)	48.5
Thickness(mm)	5.2
Height(mm)	35.2

Business data

Parameter	Data
End cover-UJ6-1.5G - 422163-Packing unit (PCS)	100
End cover-UJ6-1.5G - 422163-NW per piece(g)	1.4
End cover-UJ6-1.5G - 422163-Width(mm)	45.2
End cover-UJ6-1.5G - 422163-Thickness(mm)	2.2
End cover-UJ6-1.5G - 422163-Height(mm)	24.3