

H3A-MBK-1L/S-SE - Housing

112 003 925 1001

<https://www.wainelectric.com/h3a-mbk-1l-s-se>



Specifications:3A,Housing type:Unsealed cover,Outgoing method:Side outlet,Locking type:Single lock,Thread:NA,Housing material:Die casting zinc,Material:Stainless steel,Seals:FPM

Technical Data


Series	Anti-corrosion housing
Specifications	3A
Housing type	Unsealed cover
Housing Overview	NA
Outgoing method	Side outlet
Locking type	Single lock
Thread	NA
Housing material	Die casting zinc
Housing color	RAL 9005 (ink black)
Surface treatment	Epoxy powder coating
Interlocking method	Metal elastic connection
Material	Stainless steel
Seals	FPM
Flame retardant rating as per UL94	V0
Working temperature	-40°C...+125°C
Protection rating	IP65


2D Drawings

112 003 925 1001

WAIN


IP65/防护等级	Mark 标志	1	2	3	4	5	6
-----------	---------	---	---	---	---	---	---





技术参数:


- 材料: 压铸锌
- 表面处理: 耐腐蚀涂料
- 颜色: RAL 9005 (黑色)
- 温度范围: -40℃ ~ +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
 - 锁扣方式: 单扣
 - 材料: 不锈钢
- 出线方向: 底部出线



面板开孔图
Panel cut out

Technical specification:

- Material: zinc die-cast
- Surface: corrosion resistant
- Colour: RAL 9005(black)
- Temperature range: -40℃ ~ +125℃
- Degree of protection: IP65 (acc.to IEC 60529 for coupled connector)
- Locking element:
 - Locking type: single locking latch
 - material: stainless steel
- Cable entry: bottom entry



				表面处理 Finish				—				图号 Drawing No.		—	
				材料 Material				—				产品代号 Part Code		H3A-MBK-1L/S-SE	
				比例 Scale				1:1				产品序号 Part No.		1120039251001	
				版本 REV.				V1.1				产品名称 Part Name		—	
				重量 Weight				63.1g							
				数量 Qty.				—							
				All Dimensions in mm Original Size DIN A 4											

标记 Mark		数量 Number		变更描述/Description		签名 Signature		日期 Date	
绘图 Drawn		P YU		日期 Date		09.12.2023		标准 Stand.	
审核 Checked		Q GAO		日期 Date		09.12.2023			
工艺 Process		—		日期 Date		—		批准 Approved	
						HQ ZHANG		09.12.2023	